



BLACK

CS-Mount Cameras

7 Models Available



SIC Black CS-Mount Cameras

With 7 models to choose from, SIC Black has a CS-Mount camera for every need. We have designed all of our cameras from the ground up, to deliver the best possible performance and convenience for the dealer / installer.

Performance

- High resolution models feature UTP, Digital Noise Reduction, On Screen Display, Digital Slow Shutter, and built in motion detection
- Resolution ranging up to 580 color lines (up to 700 lines B/W)

Convenience / ease of installation

- Auto-sensing dual voltage
- Top and bottom mounting

Extras

- 3 year warranty on all cameras
- Indoor and outdoor mounting options
- Available in white or black
- OEM products for high - volume dealers

For order assistance, questions and inquiries, please contact one of our sales consultants at: 1-877-5SC-BLACK or through email at sales@sc-black.com, or please feel free to browse our website at www.sc-black.com.





BLACK

CS-Mount Cameras

7 Models Available



CS-Mount Cameras

Product	Basic	Standard	High resolution	High resolution	Day / Night	Wide dynamic range	Wide dynamic range
SKU	BLK-CCS102NB	BLK-CCS103NS	BLK-CCS114NH	BLK-CCS104NH	BLK-CDS105NH	BLK-CWS107NH	BLK-CWS108NH
Image Sensor	Sony 1/3" Super HAD Color CCD	Sony 1/3" Super HAD Color CCD	Sony 1/3" Super HAD Color CCD	Sony 1/3" Super HAD Color CCD	Sony 1/3" Super HAD Color CCD	Sony 1/3" Super HAD Color CCD	Pixim CMOS
Lens	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Zoom	N/A	N/A	N/A	10x digital zoom	10x digital zoom	10x digital zoom	N/A
Resolution	380 TVL	480 TVL	550 TVL	580 TVL	580 color / 700 B/W TVL	560 color / 700 B/W TVL	540 TVL
Effective Pixels	510(H) x 494(V), 250K (NTSC)	768(H) x 494(V), 380K (NTSC)	768(H) x 494(V), 380K (NTSC)	768(H) x 494(V), 380K (NTSC)	768(H) x 494(V), 380K (NTSC)	768(H) x 494(V), 380K (NTSC)	720(H) x 540(V)
Minimum Illumination	0.1 lux	0.5 lux	0.3 lux	0.001 lux	0.001 lux	0.001 lux	0.001 lux
IR Range	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Day / Night Function	N/A	N/A	Digital	Digital	True D/N with mechanical cut filter	True D/N with mechanical cut filter	Digital
Electronic Shutter	Auto 1/60sec - 1/100,000sec	Auto 1/60sec - 1/100,000sec	Auto 1/60sec - 1/100,000sec	Auto 1/60sec - 1/120,000sec	Auto 1/60sec - 1/120,000sec	Auto 1/60sec - 1/120,000sec	Auto 1/60sec - 1/100,000sec
Video Output	1.0V p-p / 75 ohm	1.0V p-p / 75 ohm	1.0V p-p / 75 ohm	1.0V p-p / 75 ohm	1.0V p-p / 75 ohm	1.0V p-p / 75 ohm	1.0V p-p / 75 ohm
UTP	No	No	No	Available	Available	Available	Available
Dynamic Range	48dB	48dB	50dB	52dB	52dB	52dB	50dB / 120dB max
AGC Control	Built-in	Built-in	Built-in	OSD selectable	OSD selectable	OSD selectable	OSD selectable
OSD	No	No	Yes	Yes	Yes	Yes	Yes
DSS / Range	N/A	N/A	N/A	OFF / x2 to x 256	OFF / x2 to x 256	OFF / x2 to x 256	N/A
DNR	N/A	N/A	N/A	Yes	Yes	Yes	No
Digital Image Stabilization	No	No	No	Yes	Yes	Yes	No
Weatherproof	No	No	No	No	No	No	No
Power Consumption	12VDC/24VAC - 280mA/170mA	12VDC/24VAC - 280mA/170mA	12VDC/24VAC - 280mA/170mA	12VDC/24VAC - 280mA/170mA	12VDC/24VAC - 400mA/250mA	12VDC/24VAC - 400mA/250mA	200mA
Power Requirement	12/24V dual voltage	12/24V dual voltage	12/24V dual voltage	12/24V dual voltage	12/24V dual voltage	12/24V dual voltage	12/24V dual voltage
Size	4.1" x 2.3" x 2.3", 13.5 oz.	4.1" x 2.3" x 2.3", 13.5 oz.	4.1" x 2.3" x 2.3", 13.5 oz.	4.1" x 2.3" x 2.3", 13.5 oz.	4.1" x 2.3" x 2.3", 13.5 oz.	4.1" x 2.3" x 2.3", 13.5 oz.	4.1" x 2.3" x 2.3", 13.5 oz.
Color	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory	Ivory
Sync System	Internal / line lock	Internal / line lock	Internal / line lock	Internal / line lock	Internal / line lock	Internal / line lock	Internal / line lock
Warranty	3 years	3 years	3 years	3 years	3 years	3 years	3 years

For order assistance, questions and inquiries, please contact one of our sales consultants at: 1-877-5SC-BLACK or through email at sales@sc-black.com, or please feel free to browse our website at www.sc-black.com.

