



BLACK

BLK-CCP141VH
Mini Speed Dome Camera



SIC Black **10x Zoom Mini** **Speed Dome Camera**

This mini speed dome camera is the perfect advanced solution for discreet pan, tilt and zoom functions. The surveillance camera is equipped with 1/4" Super HAD image sensor that supports 500 TVL (color) and 570 TVL (B/W) resolutions, making images crisp and clear. It supports 63 preset locations, eight scanning tours, four scans, four patterns and auto-scan function. It has four-zone image masking for privacy and is compatible with multiple protocols.

Features

- 1/4" Super HAD image sensor
- Built-in optical 10x AF zoom (f3.8 - 38mm)
- High quality images with 500 TV lines (color) and 570 TV lines (B/W)
- 360° endless panning and 0° ~ 180° tilt angle (Digital flip)
- IR cut filter removable day / night
- 63 presets, 8 tours, 4 scan, 4 pattern, autoscan
- 4 zones of image masking for privacy
- DNR technology enabled hard disk saver
- Additional balun video out
- Easy interface with multiple protocols
- ABS body and polycarbonate dome cover

For order assistance, questions and inquiries, please contact one of our sales consultants at:
1-877-5SC-BLACK or through email at sales@sc-black.com, or please feel free to browse our website at www.sc-black.com.





BLACK

BLK-CCP141VH

10x Zoom Mini Speed Dome Cameras



Specifications

Item	NTSC	PAL
Image Pick-up Device	1/4" Super HAD CCD	
Total Pixels	811 (H) x 508 (V)	795 (H) x 596 (V)
Effective Pixels	768 (H) x 494 (V)	752 (H) x 582 (V)
Scanning System	2:1 Interlace, 525 lines, 60 fields / 30 frames	2:1 Interlace, 625 lines, 50 fields / 25 frames
Horizontal Resolution	Color (wide) : 500 TV lines (min.) / B/W(wide) : 570 TV lines (min.)	
Zoom Ratio	10X, f3.8 - 38.0mm (F2.8)	
Angle Field of View	(H): Appr. 51.2° (wide) to 5.58° (tele) / (V) : Appr. 39.3° (wide) to 4.27° (tele)	
Digital Zoom	Built-in (2X ~ 10X, Total 100X zoom)	
S/N Ratio (Y signal)	50dB (AGC off, Weight on)	
Min. Illumination	0.7 lux @ F2.8 (50 IRE) : Color mode 0.02 lux @ F2.8 (50 IRE) : B/W mode	
Day and Night	Color / Auto1 / Auto2 / B/W (ICR filter change)	
White Balance	ATW / AWC / Manual selectable (1800°K ~ 10,500°K)	
Electronic Shutter Speed	Auto / Manual selectable (1/60 ~ 1/120,000)	Auto / Manual selectable (1/50 ~ 1/120,000)
Sens-up	On / Off (Selectable limit ~ 128X)	
Function	63 Presets, 8 Tours, 4 Scan, 4 Area, 4 Pattern, 2 Alarm, Autoscan	
Privacy Function	Max. 4 Programmable zones	
Preset Positions	63 Positions	
Rotation Angle	Pan : 360° Endless / Tilt : 0° ~ 180° (Digital Flip)	
Pan / Speed	Manual : 100° / sec, Turbo : 180° / sec, Preset : 360° / sec	
Flip	Digital Flip Support	
Video Output	1.0Vp-p / 75 Omega, Balun out	
Communication	RS-485	
Power consumption	DC12V / 600mA, AC24V / 550mA	
Operating Temperature	-10°C ~ +55°C	
Operating Humidity	20% ~ 75% RH	
Certification	CE, FCC, RoHS	
Dimension / Weight	0122 (W) x 145 (H) mm / 700g	

For order assistance, questions and inquiries, please contact one of our sales consultants at:
 1-877-5SC-BLACK or through email at sales@sc-black.com, or please feel free to browse our website at
 www.sc-black.com.

