

NR32P6-PI6



IP

3300 SERIES 16-CHANNEL RACK-MOUNT NVR

PROFESSIONAL IP RECORDING SOLUTION SUPPORTS LATEST H.265+ COMPRESSION FORMAT

- + 16 IP cameras
- + Integrated 16 port PoE switch with 802.3af/at support
- + 8.0 megapixel recording resolution
- + Up to 12 TB storage capacity

WHAT'S INCLUDED:

- + 3300 series 16-channel rack-mount NVR
- + (1) USB mouse
- + (1) Power supply cable
- + (1) 6' HDMI cable
- + (1) 6' CAT5e patch cable
- + (1) Set of rack mount ears



PROTECTION AND WARRANTY

All Supercircuits purchases are protected by a 30-day money-back guarantee, unlimited US-based technical support, and our 3-year warranty covers your entire purchase, with no asterisks and no exceptions.

Enjoy the convenience of plug-and-play support for compatible IP cameras up to 8.0 MP resolution with this 3300 Series 16-Channel NVR.

This NVR has 2 hard drive bays that support up to 2 x 6 TB hard drives and an incoming bandwidth of 160 Mbps to support up to 16 IP cameras. You can capture higher quality details with a recording resolution of up to 8.0 MP.

This NVR supports the latest video compression format, H.265+, which provides superior improvements in image quality and bandwidth. It also allows for faster, more fluid viewing, along with the ability to view more channels remotely. With H.265+ compression, you can store more information using fewer hard drives, which allows you to do more with less. This recorder also supports H.265, H.264+, and H.264.

The recorder comes with 1 alarm output to connect to external devices such as a siren or fire alarm. This enables trigger recording based on the camera location connected to a specific alarm/sensor.

This versatile recorder allows multiple selectable recording modes: continuous, motion detection, VCA, and event. Recording features include event search, log, and notification, as well as email notification.

The integrated 16 port PoE (Power of Ethernet) switch that supports 802.3af and 802.3at reduces the need for additional network switches and offers the highly convenient plug-and-play auto connect feature for compatible cameras.

This NVR works with the user-friendly CMS (Central Management Software), a professional monitoring platform that enables you to centrally manage all your devices, at multiple locations, from a single interface. The CMS enables you to view up to 64 live cameras, and it is loaded with powerful features that include: drag-and-drop system and camera selection, customizable displays, device grouping, alarms and notifications, and remote system management.

Free Guarding Expert iOS and Android mobile app delivers convenient remote viewing of live and recorded video via a secure Peer-to-Peer connection from the recorder to your mobile device, provided by Guarding Expert's P2P Cloud Service. You will also receive push notifications that alert you in real time to events such as motion detection, tampering or VCA events.

DISTRIBUTED BY:



SUPER | CIRCUITS

1.800.335.9777
www.supercircuits.com



1.877.797.7377
www.securitycamerasdirect.com

SPECIFICATIONS

NETWORKING

Ethernet Interface	1 RJ-45 Gigabit LAN, 16 RJ-45 10/100 PoE
Ethernet Ports	17
Protocols	TCP/IP, DHCP, P2P, DNS, DDNS, NTP, SMTP, NFS, iSCSI, UPnP™, HTTPS
Remote Configuration	Yes
Remote Viewable	Yes

RECORDING SPECIFICATIONS

Channels	16
Activity Log	Yes
Compression Type	H.265+, H.265, H.264, H.264 OVC
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Search Mode	Yes
Event Search	Yes
Recording Resolution	Up to 8 Megapixel
Max Storage Capacity (TB)	Supports up to 12TB (2 x 6TB HDD)
Frame Rate (fps)	Up to 60fps per channel
Motion Detection	Camera Dependent
Pre/Post Alarm Recording	Yes
Privacy Video Block	Yes
Recording Mode	Continuous, Motion, Event, Alarm, VCA
Video Analytics Capable	Yes
Video Offload	.mp4, .avi
Video Streaming	Dual

PHYSICAL CHARACTERISTICS

Dimensions	15.2 W" × 12.4" D × 2.0" H
Certification	FCC, CE, RoHS, UL
Hard Drive Included	No
Hard Drive Type	3.5" SATA
Number of Drive Bays	2
Operating Temperature (F)	14° ~ 131°
Product Color	Black
Weight (lb)	6.6

POWER REQUIREMENTS

Power Supply Included	Yes
PoE	(802.3af / 802.3at)
Power (w)	≤ 10W (without hard drive, PoE not used), ≤ 180W (full load); 120W max PoE output

SOFTWARE

Browser Support	Internet Explorer, Apple Safari
OS (Client)	Windows, Mac OSX
Mobile App	iOS & Android

CONNECTORS

Sensor Inputs	4
Alarm Outputs	1
Audio In	1
Audio Out	1
USB Ports	2